

KINELEC

12-18W AC-DC Current Mode Control type

LDROF-1



Features :

- Input voltage 110-270VAC
- No load power consumption very low
- Protections: Short circuit/ OL/OV
- Output available 30-70VDC
- High efficiency >84%
- High power factor >.920
- Input lead length 10 inch
- Output lead length 10 inch
- Open frame type
- 1 year warranty

LED DRIVER ROUND OPEN FRAME

Also available with IP-65,66,67&
With HPF

MODEL No	VOLTAGE IN	VOLTAGE OUT	RATED CURRENT	RATED POWER	LED 1W
KSE-LDROF18W01	130-270 VAC	40VDC	350mA	12W	1x12 LED(S)
KSE-LDROF18W01	130-270 VAC	48VDC	350mA	14W	1x14 LED(S)
KSE-LDROF18W02	130-270 VAC	51VDC	700mA	15W	1x15 LED(S)
KSE-LDROF18W01	130-270 VAC	54VDC	350mA	16W	1x16 LED(S)
KSE-LDROF18W02	130-270 VAC	58VDC	700mA	17W	1x17 LED(S)
KSE-LDROF18W01	130-270 VAC	60VDC	350mA	18W	18 LED(S)
KSE-LDROF18W02	130-270 VAC	30VDC	700mA	18W	9X2 LED(S)

In addition to the above voltage range, we can provide you with specific voltage as desired by you.

Dimension 70 x 32 mm (D-H)

Wt. 106 gms. (Approx)