

# KINELEC

## 120-240W SMPS Battery Charger

# BCAHT-2



### Features :

- Input Voltage 110V or 230VAC
- Power ON-OFF switch
- Forced Cooling Fan
- Input Voltage Range  $\pm 20\%$
- Protections: Short circuit/ overload/ over voltage
- Charging CC,CV
- Output available 14.10-56V DC
- Output Connector
- Input Main Lead 3 Pole INDIAN Type
- Enclosure Type
- 1 year warranty

### AC-DC SMPS BATTERY CHARGER

(Also available in open card)

MODEL No	VOLTAGE IN	VOLTAGE OUT	RATED CURRENT	RATED POWER	LOAD REGULATION
KSE-CHG120W01	140-270 VAC	14.10	10	140W	.1-.3V
KSE-CHG120W02	140-270 VAC	14.10	20	280W	.1-.3V
KSE-CHG120W03	140-270 VAC	21.10	6	140W	.1-.3V
KSE-CHG120W04	140-270 VAC	21.10	12	280W	.1-.3V
KSE-CHG120W01	140-270 VAC	28	5	140W	.1-.3V
KSE-CHG120W02	140-270 VAC	28	10	280W	.1-.3V
KSE-CHG120W03	140-270 VAC	56	2.5	140W	.1-.3V
KSE-CHG120W04	140-270 VAC	56	5	280W	.1-.3V

In addition to the above voltage range, we can provide you with specific voltage as desired by you.

Dimension 185 x 80 x 46 mm (L- W - H)