

KINELEC

6-8W AC-DC SMPS Battery Charger

BCAD T-1



Features :

- Universal AC input/Full range
- No load power consumption < 0.3W
- Protections: Short circuit/ OL/OV
- Charging CC, CV
- Output available 3.3-56V DC
- Output lead approx 1 mtr
- 2 pole INDIAN plug
- Fully enclosed plastic case
- 1 year warranty

AC-DC SMPS BATTERY CHARGER

(Also available in open card)

MODEL No	VOLTAGE IN	VOLTAGE OUT	RATED CURRENT	RATED POWER	LOAD REGULATION
KSE-CHG08W01	90-270 VAC	3.3	2	8W	.1-.3V
KSE-CHG08W02	90-270 VAC	7.20	1.2	8W	.1-.3V
KSE-CHG08W03	90-270 VAC	14.10	0.500mA	8W	.1-.3V
KSE-CHG08W04	90-270 VAC	21.20	0.360mA	8W	.1-.3V
KSE-CHG08W05	90-270 VAC	29.20	0.300mA	8W	.1-.3V
KSE-CHG08W06	90-270 VAC	56	0.140mA	8W	.1-.3V

In addition to the above voltage range, we can provide you with specific voltage as desired by you.

Dimension 54 x 44 x 27 mm (L- W - H)

Wt. 70 gms. (Approx)