

KINELEC

16-20W AC-DC SMPS Battery Charger

BCDTT-1



Features :

- Universal AC input/Full range
- No load power consumption < 0.3W
- Protections: Short circuit/ overload/ over voltage
- Charging CC, CV
- Output available 3.3-56V DC
- Output lead approx 1 mtr
- 2 pole INDIAN plug
- Fully enclosed plastic case
- 1 year warranty

AC-DC SMPS BATTERY CHARGER

(Also available open card)

MODEL No	VOLTAGE IN	VOLTAGE OUT	RATED CURRENT	RATED POWER	LOAD REGULATION
KSE-CHG18W01	90-270 VAC	3.3	3	18W	.1-.3V
KSE-CHG18W02	90-270 VAC	7.20	3	18W	.1-.3V
KSE-CHG18W03	90-270 VAC	14.10	1.5	18W	.1-.3V
KSE-CHG18W04	90-270 VAC	21.20	0.800mA	18W	.1-.3V
KSE-CHG18W05	90-270 VAC	29.20	0.650mA	18W	.1-.3V
KSE-CHG18W06	90-270 VAC	56	0.320mA	18W	.1-.3V

In addition to the above voltage range, we can provide you with specific voltage as desired by you.

Dimension 105 x 49 x 32 mm (L- W - H)

Wt. 170 gms. (Approx)