

KINELEC

9W DC-DC Single Output Dip Package

DCDPT-1



Features :

- Input Voltage Range 3.2-36VDC
- Protections: Short circuit/ overload/ over voltage,CC,CV
- Output available 3.2-30VDC
- Rugged Plastic Body
- 1 year warranty
- Water Proof
- Output Non Isolated

Dimension 42 x 22 x 17 mm (L- W - H)

Wt. 24 gms. (Approx)

DC-DC CONVERTER NON ISOLATED

MODEL No	VOLTAGE IN	VOLTAGE OUT	RATED CURRENT (Approx)	RATED POWER	LOAD REGULATION
KSEDCNIP9W01	3.2-6VDC	3.3	1.5	9W	.1-.3V
KSEDCNIP9W02	3.2-6VDC	5	1.5	9W	.1-.3V
KSEDCNIP9W03	3.2-6VDC	9	1	9W	.1-.3V
KSEDCNIP9W04	3.2-6VDC	12	0.600mA	9W	.1-.3V
KSEDCNIP9W05	3.2-6VDC	18	0.400mA	9W	.1-.3V
KSEDCNIP9W06	9-14VDC	5	1.5	9W	.1-.3V
KSEDCNIP9W07	9-14VDC	9	1	9W	.1-.3V
KSEDCNIP9W08	9-14VDC	12	0.600mA	9W	.1-.3V
KSEDCNIP9W09	9-14VDC	18	0.400mA	9W	.1-.3V
KSEDCNIP9W10	9-14VDC	24	0.350mA	9W	.1-.3V
KSEDCNIP9W11	9-14VDC	28	0.300mA	9W	.1-.3V
KSEDCNIP9W12	16-21VDC	5	1.5	9W	.1-.3V
KSEDCNIP9W13	16-21VDC	9	1	9W	.1-.3V

In addition to the above voltage range, we can provide you with specific voltage as desired by you.

KSEDCNIP9W14	16-21VDC	12	0.600mA	9W	.1-.3V
KSEDCNIP9W15	16-21VDC	18	0.400mA	9W	.1-.3V
KSEDCNIP9W16	16-21VDC	24	0.350mA	9W	.1-.3V
KSEDCNIP9W17	16-21VDC	28	0.300mA	9W	.1-.3V
KSEDCNIP9W18	21-28VDC	5	1.5	9W	.1-.3V
KSEDCNIP9W19	21-28VDC	9	1	9W	.1-.3V
KSEDCNIP9W20	21-28VDC	12	0.600mA	9W	.1-.3V
KSEDCNIP9W21	21-28VDC	18	0.400mA	9W	.1-.3V
KSEDCNIP9W22	21-28VDC	24	0.350mA	9W	.1-.3V
KSEDCNIP9W23	21-28VDC	28	0.300mA	9W	.1-.3V

In addition to the above voltage range, we can provide you with specific voltage as desired by you.