

# KINELEC

30W DC-DC LED Driver

# DCLDT-2



### Features :

- Input voltage available 12-56VDC
- Protections: Short circuit/ OL/OV/CC
- Output available 32-48V DC
- Output connector
- Input connector
- Open PCB Card type
- 1 year limited warranty
- Available with IP-65, 66, 67

### DC-DC LED DRIVER (Also available in plastic housing)

Dimension 113 x 54 x 32 mm (L- W - H)  
Wt. 150 gms. (Approx)

MODEL No	VOLTAGE IN	VOLTAGE OUT	RATED CURRENT	RATED POWER	LED 1W
KSE-DCLD30W01	10.5-15VAC	32VDC	1.050Am	30W	1X10X3 LED(S)
KSE-DCLD30W02	10.5-15VAC	48VDC	0.700mA	30W	1X15X2 LED(S)
KSE-DCLD30W03	16-21VAC	32VDC	1.050Am	30W	1X10X3 LED(S)
KSE-DCLD30W04	16-21VAC	48VDC	0.700mA	30W	1X15X2 LED(S)
KSE-DCLD30W05	22-28VAC	32VDC	1.050Am	30W	1X10X3 LED(S)
KSE-DCLD30W06	22-28VAC	48VDC	0.700mA	30W	1X15X2 LED(S)

In addition to the above voltage range, we can provide you with specific voltage as desired by you.